

July 2025

## HYUNDAI PERFORMANCE ENGINE OIL 15W-40 CK-4

Premium high performance multigrade, heavy-duty diesel engine oil specifically designed for new low emission model. It is also recommended for a wide range of diesel engines requiring the latest API CK-4, ACEA E9 performance lubricants operating under the most severe service conditions.

### Specifications, Approvals & Recommendations

- API CK-4
- ACEA E7, E9, E11
- HD HCE EO-E1

For a full listing of equipment approvals and recommendations, please consult your local representative.

### Typical Physical Characteristics

PROPERTIES	METHOD	HYUNDAI PERFORMANCE ENGINE OIL 15W-40
Kinematic Viscosity @40°C	ASTM D445	115 mm <sup>2</sup> /s
Kinematic Viscosity @100°C	ASTM D445	15.3 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	139
Density @15°C	ISO 12185	876 kg/m <sup>3</sup>
Pour Point	ASTM D97	-35°C
Flash Point	ASTM D92	236°C
Sulphated Ash	ASTM D874	1% Maximum
Total Base Number		10 mg KOH/g

These characteristics are typical of current production. Whilst future production will conform to Hyundai's specification, variations in these characteristics may occur.

### Health, Safety & Environment

- **Health and Safety**
  - This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene and maintained.
  - Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Safety Data Sheet.
- **Protect the environment**
  - Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

